

Number of doors			3
Engine			Petrol 1.5L VVT
Drive system			ALLGRIP PRO
Transmission			LCV (5MT)
<b>DIMENSIONS</b>			
Overall length	Front bumper to rear bumper	mm	3,480
	Front bumper to spare wheel cover	mm	3,645
Overall width			mm 1,645
Overall height			mm 1,720
Wheelbase			mm 2,250
Tread	Front	mm	1,395
	Rear	mm	1,405
Minimum turning radius			m 4.9
Minimum ground clearance			mm 210
Approach angle			deg. 37
Ramp breakover angle			deg. 28
Departure angle			deg. 49
<b>CAPACITIES</b>			
Seating capacity	persons		2
Luggage capacity	Max. volume	litres	863
Fuel tank capacity	litres		40
<b>ENGINE</b>			
Type			K15B
Number of cylinders			4
Number of valves			16
Piston displacement	cm3		1462
Bore x stroke	mm		74.0 x 85.0
Compression ratio			10
Maximum output	kW/rpm		75/6,000
Maximum torque	N·m/rpm		130/4,000
Fuel distribution			Multipoint injection
<b>TRANSMISSION</b>			
Type			5MT
Gear ratio	1st		4.425
	2nd		2.304
	3rd		1.674
	4th		1.190
	5th		1.000
	Reverse		5.151
Final gear ratio			4.090
Transfer gear ratio	High		1.000
	Low		2.002
<b>CHASSIS</b>			
Steering			Recirculating ball
Brakes	Front		Solid disc
	Rear		Drum, leading and trailing
Suspension	Front		3-link rigid axle with coil spring
	Rear		3-link rigid axle with coil spring
Tyres			195/80R15
<b>WEIGHTS</b>			
Kerb weight (min./with full options)	kg		1,090
Gross vehicle weight	kg		1,435
<b>PERFORMANCE</b>			
Maximum speed	km/h		145
<b>ENVIRONMENTAL PERFORMANCE</b>			
Emission standard compliance			Euro 6
Fuel consumption (NEDC)*2	Urban	litres/100km	(Low / High) 7.2
	Extra-urban	litres/100km	(Low / High) 5.4
	Combined	litres/100km	(Low / High) 6.1
CO2 emissions (NEDC)*2	g/km		(Low / High) 138
CO2 emissions (WLTC)*3	g/km		(Low) 173(High) 174